



# Essential SmartBright Solar Flood Light

## BVC080 LED30/730 Solar

Solar flood light with lithium ferro phosphate battery built in the luminaire, Remote controller and installation accessories included. IP65, plastic housing. Available in 600, 900, 1500, 2500, 3000 and 4000 Lumens

### Warnings and Safety

- Install the luminaire in a sunny place that is not shaded by trees, buildings and walls, then the solar panel can receive the maximum sunlight for charging the battery.
- Charge the product under sunlight for at least 8 hours before first time using.
- This luminaire does not need any external electrical connection. It works 100% on solar energy.

### Product data

General Information		Grid connection type	
Driver included	Yes		Off grid
Light Technical		Controls and Dimming	
Luminous Flux	3,000 lm	Dimmable	No
Correlated Color Temperature (Nom)	3000 K	Configurability	Not configurable
Color rendering index (CRI)	70	Solar dimming profile	Pre-configured
Operating and Electrical		Mechanical and Housing	
Battery type	LiFePO4	Housing Color	Grey
Battery ampere hour	19 Ah	Overall length	290 mm
Battery voltage	3.2 V	Overall width	249 mm
Battery charging & discharging cycles	500	Overall height	49 mm
Panel type	Mono crystalline	Dimensions (Height x Width x Depth)	49 x 249 x 290 mm
Panel voltage	5 V	Material	Acrylonitrile-butadiene-styrene
Panel peak wattage	20 W	Battery location	In built
		Ingress protection code	IP65 [Dust penetration-protected, jet-proof]

# Essential SmartBright Solar Flood Light

Optical cover type	Glass
Net Weight (Piece)	3.700 kg
<b>Approval and Application</b>	
Ambient temperature range	0 °C to 50 °C
<b>Product Data</b>	
Order product name	BVC080 LED30/730 Solar
Full product name	BVC080 LED30/730 Solar

Full product code	692382867166299
Order code	911401875302
Material Nr. (12NC)	911401875302
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	6923828671662
Numerator - Packs per outer box	5
EAN/UPC - Case	6923828671723

## Dimensional drawing

